

## Intermediate maintenance (C markets\*) Cayman GT4 (981) as of 2015 model

	Work instruction	
Vehicle Ident. No.	for order no.	
□ Intermediate maintenance		
	/ 12000, 36000, 60000, 84000 miles etc.	
	nce tasks, see PIWIS Information System Workshop Manual	1
	ot reached, intermediate maintenance must be carried out aft	
10 years.		
	ubsequent work, such as adjusting, readjusting, correcting an	
topping up, but does not include repairing, rep	placing and reconditioning parts or assemblies.	<b> </b> ✓
Electrics		
Windscreen wiper/washer system, headlight of	cleaning system: check function	
Horn: check function		
Tyres: check tyre pressure (TPM)		
Diagnostic system: read out fault memory; res	set maintenance interval	
Inside the vehicle		
Particle filter: replace filter element		
Front luggage compartment		
	nt lid to ensure that they are secure and function properly	
Replace air intake pre-filter		
	level; check window cleaner and antifreeze, depending on ti	ime of
year, only use windscreen cleaners approved		
Outside the vehicle		
Check wiper blades		
All headlights: check adjustment		
Radiators and air intakes: visual inspection for	r external contamination and blockage	
Under the vehicle		
Drain engine oil		
Change oil filter		
Tyres: check condition		
Visual inspection for leaks from underneath (c	oils and other fluids)	
Brake lines: visual inspection for damage, rou	ting and corrosion	
Brake system: check brake pads and brake di		
Brake hoses: visual inspection for damage		
Drive shafts: visual inspection of the boots for	leaks and damage	
Check that threaded connections for chassis a	adjustment at front and rear are secure	
Check vehicle height		
Control boxes for exhaust flaps: check functio	n	
Rear luggage compartment		
Fill in engine oil		
Coolant: check level and antifreeze		
Check rubber stops on rear lid		

<sup>\*</sup> For country allocation, see overview of A, B and C markets



## Intermediate maintenance (C markets\*) Cayman GT4 (981) as of 2015 model

Vehicle Ident. No.	Work instruction for order no.	
☐ Additional maintenance every 2 years (Labour operation: 03 51 00)		
Change brake fluid (use only original Porsche brake	fluid)	
Prepare condition report for long-life guarantee		
Tyre sealing compound: check use-by date and replace if necessary		
☐ Additional maintenance for drive belt		
(Labour operation: 03 60 00)		
Check drive belt, at 60,000 km/36,000 miles or every		
Check drive belt, at 140,000 km/84,000 miles or every 10 years		
Check drive belt, at 220,000 km/132,000 miles or every 16 years		
☐ Additional maintenance for spark plugs		
every 20000 km / 12000 mls or every 4 yea	rs	
(Labour operation: 03 81 00)		
Replace spark plugs		
☐ Additional maintenance every 80000 km /	48000 mls or every 6 years	
(Labour operation: 03 82 00)		
Air cleaner: replace filter elements		
Replace drive belt		
☐ Additional maintenance every 120000 km (Labour operation: 03 85 00)	72000 mls or every 4 years	
Ancillary unit mounts and chassis: visual inspection of	of all rubber mountings and boots for damage	
☐ Additional maintenance every 180000 km	/ 108000 mls or every 12 years	
(Labour operation: 03 88 00)		
Manual transmission: change oil		
Signature (mechanic):		
Test drive:		
	nd foot brake (also actuation travel), engine, clutch, steering, TC Off switch, PASM switch, sports exhaust system, Automatic and instruments: check function	
Signature (final check):		
	Porsche Centre	